



Dee Shackles with Screw Collar Pin G-4151

Product information

Dee shackle with screw collar pin.

Certification: This product can be supplied with a works certificate, 3.1 material certificate, manufacturer test certificate, EC Declaration of Conformity. All shackles starting from 2 t can be supplied with DNV 2.7-1 certificate.

Standard: EN 13889 and meets performance requirements of US Fed. Spec. RR-C-271 Type IVB Class 2, Grade A.

Material: Bow and pin high tensile steel, quenched and tempered

Marking: According to standard, CE-marked

Temperature range: -40°C up to +200°C

Finish: Hot dip galvanized

Standard: EN 13889

Safety factor: 6:1

Grade: 6

Part Code	WLL ton	A mm	B mm	C mm	D mm	e mm	f mm	g mm	h mm	Weight kg
420100030680	0.33	5	6	12	5	9,5	19	33	29,5	0.02
420100050680	0.5	7	8	16,5	7	12	22	41,5	38	0.05
420100080680	0.75	9	10	20	9	13,5	26	50	46,5	0.09
420100100680	1	10	11	22,5	10	17	32	59	54	0.14
420100150680	1.5	11	13	26,5	11	19	37	68	59,5	0.19
420100200680	2	13,5	16	34	13	22	43	81	73	0.32
420100330680	3.25	16	19	40	16	27	51	97	89	0.54
420100480680	4.75	19	22	46	19	31	59	112	103	0.87
420100650680	6.5	22	25	52	22	36	73	134	119	1.34
420100850680	8.5	25	28	59	25	43	85	154	137	2.08
420100950680	9.5	28	32	66	28	47	90	167	153	2.77
420101200680	12	32	35	72	32	51	94	180	170	3.72
420101350680	13.5	35	38	80	35	57	115	209	186	5.14
420101700680	17	38	42	88	38	60	127	230	203	6.85
420102500680	25	45	50	103	45	74	149	271	243	11.45
420103500680	35	50	57	111	50	83	171	305	272	16.86
420104250680	42.5	57	65	130	57	95	190	345	310	24.61
420105500680	55	65	70	145	65	105	203	376	344	32.65

Blueprint

