


Offshore crane



Piling crane




Mobile port crane



Steel Wire Rope Verotop P

Product information



Wire rope construction: Verotop P is a rotation-resistant rope with compacted strands and a rope core covered with a plastic layer.

Features:

- Very high breaking strength.
- Provides a very stable rope structure and achieves excellent bending fatigue results.
- Offers excellent crushing and very good abrasion resistance.
- Possesses perfect spooling behavior on multilayer drum.

ISO 4309 Rope Category No: All Diameters **RCN.23-3.**

Marking: According to standard

Standard: EN 12385-4

Note: verotop P can be used either with or without swivel.

Fill factor: 0.73

RCN: 23-3

Tolerance Ø: +2% to +4%

Part Code	Rope Diameter, mm	Steel area mm ²	Min. Breaking force	Min. Breaking force	Finish	Weight kg/100m
			kN. 1960 N/mm ²	kN. 2160 N/mm ²		
104101606070149	16	147	241.7	252.7	Bright	125
104101706070149	17	166	272.8	285.3	Bright	141
104101806070149	18	186	305.8	319.8	Bright	158

104101906070149	19	207	340.8	356.3	Bright	176
104102006070149	20	229	377.6	394.8	Bright	195
104102106070149	21	253	416.3	435.3	Bright	215
104102206070149	22	277	456.9	477.7	Bright	236
104102246070149	22.4	283	473.6	495.3	Bright	240
104102306070149	23	303	499.3	522.2	Bright	258
104102406070149	24	330	543.7	568.6	Bright	281
104102506070149	25	358	590	616.9	Bright	305
104102546070149	25.4	370	609	636.8	Bright	314
104102606070149	26	388	638.1	667.3	Bright	329
104102706070149	27	418	688.1	719.6	Bright	355
104102806070149	28	449	740.1	773.9	Bright	382
104102866070149	28.6	469	772.1	807.4	Bright	399
104102906070149	29	482	793.9	830.1	Bright	409.9
104103006070149	30	516	849.6	888.4	Bright	439
104103106070149	31	551	907.1	948.6	Bright	468
104103206070149	32	587	966.6	1011	Bright	499
104103306070149	33	624	1028	1075	Bright	531
104103406070149	34	663	1091	1141	Bright	563
104103506070149	35	702	1156	1209	Bright	597
104103606070149	36	743	1223	1279	Bright	632
104103806070149	38	828	1363	1425	Bright	704
104104006070149	40	917	1510	1579	Bright	780

104104206070149	42	1,011	1665	1741	Bright	860
104104306070149	43	1,060	1745	1825	Bright	901
104104406070149	44	1,110	1827	1911	Bright	944
104104506070149	45	1,161	1911	1999	Bright	987
104104606070149	46	1,213	1997	2089	Bright	1,031
104104806070149	48	1,321	2175	2274	Bright	1,123
104105006070149	50	1,433	2360	2468	Bright	1,218
104105206070149	52	1,550	2552	2669	Bright	1,318
104105406070149	54	1,671	2753	2878	Bright	1,421

Technical data