

Lever Hoist Elephant YA



Product information

YA Series lever hoists are robust and suitable for lifting, pulling, spanning and clamping in any directions.

A solid and compact design with special rust-resistant coating performs in extreme environments such as the offshore and mining industries. The gears are completely enclosed and make the hoist highly reliable and durable meaning lower maintenance costs. One-touch change lever further improves work efficiency. Tough black body resists scratches and prevents rust. Waterproof, shock resistant gear and brake cover. The bolted rubber grip ensures safe operation of the lever hoist.

Material: Durable all steel construction.

Marking: According to standard

Temperature range: -20°C up to +60°C.

Finish: Powder coated finish and plated frame components.

Standard: EN 13157, EN 818-7

Safety factor: 4:1

Part Code	Code	Diameter mm	WLL ton	Lifting height m	Hand effort to lift full load kg	A mm	B mm	C mm	D mm	E mm	F mm	G mm	H mm	Weight kg
500500050300240	YA-50	4.3	0.5	3	37	44	69	92	240	24	36	13	180	2.8
500500080300240	YA-80	5.6	0.8	3	30	53	91	122	290	23	36	15	268	6
500500160300240	YA-160	7.1	1.6	3	36	63	99	136	352	29	43	21	310	9.2
500500320300240	YA-320	9	3.2	3	44	82.5	104	180	420	36	53	28	310	15.5
500500630300240	YA-630	9	6.3	3	45	82.5	104	235	564	47	70	34	310	26.5
500500900300240	YA-900	9	9	3	46	82.5	104	300	689	73	85	47.5	310	42

Blueprint

