



Lifting Point Pewag PLZW Zeta

Product information



Lifting Point PLZW Zeta can be assembled and disassembled without tools (Up to thread size M24). The lifting point allows full 360° rotation, comes with five-fold security against breakage and can be loaded in all directions.

The PLZW Zeta protects the surface of the load from damage by integrating a sleeve. The replaceable bolt is 100% crack tested and has a chrome-VI-free corrosion protection as well as a marking with load capacity, thread size and tightening torque.

Material: Alloy steel

Marking: CE-marked

Temperature range: -20 °C to +200 °C

Finish: painted, bolt Cr6- free galvanized

Safety factor: 5:1

Part Code	Code	WLL ton	Thread mm	a mm	b mm	c mm	d mm	e mm	f mm	g mm	n mm	n max mm	Weight kg
421525084	PLZW 0,4T	0.4	M8x12	40	64	29	14	34	30	77	12	80	0.3
421536187	PLZW 0,63T	0.63	M10x15	40	64	29	14	34	30	77	15	100	0.3
421528020	PLZW 0,95T	0.95	M12x18	40	64	29	14	34	30	77	18	180	0.3
421528336	PLZW 1,8T	1.8	M16x24	50	83	43	19	50	45	112	24	260	0.9
421528337	PLZW 2,5T	2.5	M20x30	50	83	43	19	50	45	112	30	330	0.95
421528349	PLZW 4T	4	M24x36	70	121	64	28	69	68	161	36	355	2.8
421528351	PLZW-FIX 6,3T	6.3	M30	70	121	64	28	69	68	161	45	355	3
421527136	PLZW-FIX 10T	10	M36	110	183	106	38	114	108	259	59	328	10.8
421527161	PLZW-FIX 13T	13	M42	110	183	106	38	114	108	259	69	328	11.1
421528011	PLZW-FIX 15T	15	M48	110	183	106	38	114	108	259	74	328	11.2

Blueprint

