



Lifting Point Pewag PLZW Zeta

Product information



Lifting Point PLZW Zeta can be assembled and disassembled without tools (Up to thread size M24). The lifting point allows for full 360° rotation, comes with five-fold security against breakage and can be loaded in all directions.

Marking: CE-marked

Temperature range: -20 °C to +200 °C

| Part Code | Code | WLL ton | Thread mm | a mm | b mm | c mm | d mm | e mm | f mm | g mm | n mm | n max mm | Weight kg |
|-----------|---------------|---------|-----------|------|------|------|------|------|------|------|------|----------|-----------|
| 421525084 | PLZW 0,4T | 0.4 | M8 | 40 | 64 | 29 | 14 | 34 | 30 | 77 | 12 | 80 | 0.3 |
| 421536187 | PLZW 0,63T | 0.63 | M10 | 40 | 64 | 29 | 14 | 34 | 30 | 77 | 15 | 100 | 0.3 |
| 421528020 | PLZW 0,95T | 0.95 | M12 | 40 | 64 | 29 | 14 | 34 | 30 | 77 | 18 | 180 | 0.3 |
| 421528336 | PLZW 1,8T | 1.8 | M16 | 50 | 83 | 43 | 19 | 50 | 45 | 112 | 24 | 260 | 0.9 |
| 421528337 | PLZW 2,5T | 2.5 | M20 | 50 | 83 | 43 | 19 | 50 | 45 | 112 | 30 | 330 | 0.95 |
| 421528349 | PLZW 4T | 4 | M24 | 70 | 121 | 64 | 28 | 69 | 68 | 161 | 36 | 355 | 2.8 |
| 421528351 | PLZW-FIX 6,3T | 6.3 | M30 | 70 | 121 | 64 | 28 | 69 | 68 | 161 | 45 | 355 | 3 |
| 421527136 | PLZW-FIX 10T | 10 | M36 | 110 | 183 | 106 | 38 | 114 | 108 | 259 | 59 | 328 | 10.8 |
| 421527161 | PLZW-FIX 13T | 13 | M42 | 110 | 183 | 106 | 38 | 114 | 108 | 259 | 69 | 328 | 11.1 |
| 421528011 | PLZW-FIX 15T | 15 | M48 | 110 | 183 | 106 | 38 | 114 | 108 | 259 | 74 | 328 | 11.2 |

Blueprint

