

## Web Lashing POWERTEX Trucker r-PET

### Product information



The POWERTEX Trucker r-PET lashing is a 2-part lashing and used for professional haulers.

The lashing is made from **recycled** high-strength polyester (r-PET) yarn, Cr6 free steel ratchets and hooks. Because the webbing is made from r-PET yarn, this product has a **42% CO<sub>2</sub> reduction\*** compared to the standard Trucker Lashing.

This lashing is part of Lifting Solution Group's [Aspire range™](#). In November 2023, this product won the prestigious LEEA Sustainable Award.

**Sustainability Fact Sheet Available** (see tab documents drop-down menu)

Suitable for professional transporters looking for extra high strength and durability in a web lashing.

- Strong and durable with LC 2500 daN and STF 350 daN
- Webbing has min. breaking strength of 7500 daN
- Blue webbing with 2500 daN print for easy identification
- Both the long part and short part carry blue identification labels
- Label gives information on STF and lashing capacity for different lashing connections
- Each part is marked with a unique serial number for safe equipment registration
- The blue information label is protected by a layer of transparent plastic for long life
- Year/Month calendar printed on the label where latest inspection date can be marked or punched
- All lashings carry a white label with important warning instructions and user instruction pictogram, and information about the Aspire Range™
- Each lashing is marked with QR code to access the full user manual
- Cr6 free galvanization – better for health and environment
- Trucker can be supplied with other lengths and other end fittings on request.

**Safety factor:** Webbing min. 3, ratchets min. 2 and hooks min. 2

\*A 3rd party climate LCA with a cradle-to-gate perspective according to ISO14067 has shown that our r-PET web lashings have 42% fewer CO<sub>2</sub>e emissions than our standard product. This means that our products are not only better for the environment but also make a positive

contribution to reducing CO2 emissions.

**Material:** 100% polyester (PES) high tenacity multifilament made from r-PET (recycled PET), and Steel.

**Marking:** According to standard

**Temperature range:** -40°C up to +120°C

**Standard:** EN 12195-2

**Warning:** Protect the lashings from sharp edges

Part Code	LC daN	2xLC (daN)	Length m	Band width mm	Design	Fitting	Colour	Weight kg
701401002200250	2,500	5,000	10	50	2-part	Wire hook double	Blue	2.75