

Wall Jib Crane Overbraced 180° PMT

Product information



General

Appropriate for an indoor or outdoor use, the beam of the PMT is built on an I beam profile. Its light weight gives it great flexibility for rotations of 180°. The structure of this jib crane is suitable for the optional installation of a hoist motor direction. The PMT are delivered with standard mounting brackets and our mounting kits KITFIX (optional) ensure safe anchorages for specific supports.

A full range of accessories is available.

Options

- Hoist power supply cable + lockable main switch
- Standpipe
- Rotation slowing device (adaptable without welding or mechanical intervention)
- Hot dip galvanizing (contact us)
- Rotation stops to weld onto the assembly
- Single- or multi-position rotation lock
- Outdoor use
- Electric or manual hoist

Part Code	WLL ton	Cap. kg	Span m 2,0	Span m 2,5	Span m 3,0	Span m 3,5	Span m 4,0	Span m 4,5	Span m 5,0	Span m 5,5	Span m 6,0	Span m 6,5	Span m 7,0	Span m 7,5
6025	0.15	150	•	•	•	•	•	•	•	•	•	•	•	•
6025	0.25	250	•	•	•	•	•	•	•	•	•	•	•	•
6025	0.5	500	•	•	•	•	•	•	•	•	•	•	•	•
6025	1	1,000	•	•	•	•	•	•	•	•	•	•	•	•
6025	1.6	1,600	•	•	•	•	•	•	•	•	•	-	-	-
6025	2	2,000	•	•	•	•	•	•	•	•	•	-	-	-

