

Wall Jib Crane Overbraced 180° PMT

Product information



General

Appropriate for an indoor or outdoor use, the beam of the PMT is built on an I beam profile. Its light weight gives it great flexibility for rotations of 180°. The structure of this jib crane is suitable for the optional installation of a hoist motor direction. The PMT are delivered with standard mounting brackets and our mounting kits KITFIX (optional) ensure safe anchorages for specific supports.

A full range of accessories is available.

Options

- Hoist power supply cable + lockable main switch
- Standpipe
- Rotation slowing device (adaptable without welding or mechanical intervention)
- Hot dip galvanizing (contact us)
- Rotation stops to weld onto the assembly
- Single- or multi-position rotation lock
- Outdoor use
- Electric or manual hoist

| Part Code | WLL ton | Cap. kg | Span m 2,0 | Span m 2,5 | Span m 3,0 | Span m 3,5 | Span m 4,0 | Span m 4,5 | Span m 5,0 | Span m 5,5 | Span m 6,0 | Span m 6,5 | Span m 7,0 | Span m 7,5 |
|-----------|---------|---------|------------|------------|------------|------------|------------|------------|------------|------------|------------|------------|------------|------------|
| 6025 | 0.15 | 150 | • | • | • | • | • | • | • | • | • | • | • | • |
| 6025 | 0.25 | 250 | • | • | • | • | • | • | • | • | • | • | • | • |
| 6025 | 0.5 | 500 | • | • | • | • | • | • | • | • | • | • | • | • |
| 6025 | 1 | 1,000 | • | • | • | • | • | • | • | • | • | • | • | • |
| 6025 | 1.6 | 1,600 | • | • | • | • | • | • | • | • | • | - | - | - |
| 6025 | 2 | 2,000 | • | • | • | • | • | • | • | • | • | - | - | - |

