

Wall Jib Crane Underbraced 180° PMI

Product information



The headroom is the main asset of the PMI. Its I beam profile allows to consider installation of a hoist with electric or manual steering. The PMI are delivered with standard mounting brackets and our mounting kits KITFIX (optional) ensure safe anchorages for specific supports.

A full range of accessories is available.

Options

- Hoist power supply cable + lockable main switch
- Standpipe
- Rotation slowing device (adaptable without welding or mechanical intervention)
- Hot dip galvanizing (contact us)
- Rotation stops to weld onto the assembly
- Single or multipositions rotation lock
- Outdoor use
- Motorization
- Electric or manual hoist

Part Code	WLL ton	Cap. kg	Span m 2,0	Span m 2,5	Span m 3,0	Span m 3,5	Span m 4,0	Span m 4,5	Span m 5,0	Span m 5,5	Span m 6,0	Span m 6,5	Span m 7,0
6025	0.15	150	•	•	•	•	•	•	•	•	•	•	•
6025	0.25	250	•	•	•	•	•	•	•	•	•	•	•
6025	0.5	500	•	•	•	•	•	•	•	•	•	•	•
6025	1	1,000	•	•	•	•	•	•	•	•	•	•	•
6025	1.6	1,600	•	•	•	•	•	•	•	•	•	-	-
6025	2	2,000	•	•	•	•	•	•	•	•	•	-	-
6025	2.5	2,500	•	•	•	•	•	•	•	-	-	-	-
6025	3.2	3,200	•	•	•	•	•	•	•	-	-	-	-
6025	4	4,000	•	•	•	•	•	•	•	-	-	-	-

Technical data

Outreach (m) / Capacity (kg)	2	2,5	3	3,5	4	4,5	5	5,5	6	6,5
150	x	x	x	x	x	x	x	x	x	x
250	x	x	x	x	x	x	x	x	x	x
500	x	x	x	x	x	x	x	x	x	x
1000	x	x	x	x	x	x	x	x	x	x
1600	x	x	x	x	x	x	x	x	x	
2000	x	x	x	x	x	x	x	x	x	
2500	x	x	x	x	x	x	x			
3200	x	x	x	x	x	x	x			
4000	x	x	x	x	x	x	x			