

Wall Jib Crane Articulated PMA

Product information



This articulated jib crane has a very reduced headroom. His first arm can rotate 180° degrees and the second 300°. The articulated structure facilitates the movement of loads in a cluttered environment. This model is restricted to only manual rotations.

The PMA are delivered with standard mounting brackets and our mounting kits KITFIX (optional) ensure safe anchorages for specific supports.

A full range of accessories is available.

Options

- Hoist power supply cable + lockable main switch
- Standpipe
- Rotation slowing device (adaptable without welding or mechanical intervention)
- Option of a slowing device on each arm
- Hot dip galvanizing (contact us)
- Rotation stops to weld onto the assembly
- Single- or multipositions rotation lock (arm 1 only)
- Electric or manual hoist
- Outdoor use

| Part Code | WLL | Cap. kg | Span m 2,0 | Span m 2,5 | Span m 3,0 | Span m 3,5 | Span m 4,0 | Span m 4,5 | Span m 5,0 |
|-----------|-------|---------|------------|------------|------------|------------|------------|------------|------------|
| 6025 | 0.125 | 125 | • | • | • | • | • | • | • |
| 6025 | 0.25 | 250 | • | • | • | • | • | • | • |

Technical data

| Outreach (m) / Capacity (kg) | 2 | 2,5 | 3 | 3,5 | 4 | 4,5 | 5 |
|---------------------------------|---|-----|---|-----|---|-----|---|
| 125 | x | x | x | x | x | x | x |
| 250 | x | x | x | x | x | x | x |