

## Pillar Jib Crane Underbraced 270° PFI



### Product information

The headroom is the main asset of the PFI. Its I beam profile allows to consider installation of a hoist with electric or manual steering. Floor fixing is effected by chemical anchors or anchor rods with foundation. A full range of accessories is available.

### Options

- Installation template + anchor rods (or base plate for chemical anchors, keeping its limitations in mind)
- Hoist power supply cable
- Lockable main switch
- Rotation slowing device (adaptable without welding or mechanical intervention)
- Hot dip galvanizing (contact us)
- Rotation stops to weld onto the assembly, or adjustable
- Single or multipositions rotation lock
- Outdoor use
- Electric or manual hoist

| Part Code | WLL ton | Cap. kg | Span m 2,0 | Span m 2,5 | Span m 3,0 | Span m 3,5 | Span m 4,0 | Span m 4,5 | Span m 5,0 | Span m 5,5 | Span m 6,0 | Span m 6,5 | Span m 7,0 |
|-----------|---------|---------|------------|------------|------------|------------|------------|------------|------------|------------|------------|------------|------------|
| 6025      | 0.15    | 150     | •          | •          | •          | •          | •          | •          | •          | •          | •          | •          | •          |
| 6025      | 0.25    | 250     | •          | •          | •          | •          | •          | •          | •          | •          | •          | •          | •          |
| 6025      | 0.5     | 500     | •          | •          | •          | •          | •          | •          | •          | •          | •          | •          | •          |
| 6025      | 1       | 1,000   | •          | •          | •          | •          | •          | •          | •          | •          | •          | -          | -          |
| 6025      | 1.6     | 1,600   | •          | •          | •          | •          | •          | •          | •          | -          | -          | -          | -          |
| 6025      | 2       | 2,000   | •          | •          | •          | •          | •          | •          | •          | -          | -          | -          | -          |

## Technical data

| Outreach<br>(m) /<br>Capacity<br>(kg) | 2 | 2,5 | 3 | 3,5 | 4 | 4,5 | 5 | 5,5 | 6 | 6,5 | 7 |
|---------------------------------------|---|-----|---|-----|---|-----|---|-----|---|-----|---|
| 150                                   | x | x   | x | x   | x | x   | x | x   | x | x   | x |
| 250                                   | x | x   | x | x   | x | x   | x | x   | x | x   | x |
| 500                                   | x | x   | x | x   | x | x   | x | x   | x | x   | x |
| 1000                                  | x | x   | x | x   | x | x   | x | x   | x |     |   |
| 1600                                  | x | x   | x | x   | x |     |   |     |   |     |   |
| 2000                                  | x | x   | x | x   | x |     |   |     |   |     |   |