

Pillar Jib Crane Articulated PFA

Product information

Appropriate for an indoor or outdoor use, this articulated jib crane has a very reduced headroom. The first arm can rotate 270° and the second 300°. The articulated structure facilitates the movement of loads in a cluttered environment. This model is restricted to only manual rotations.

Floor fixing is effected by chemical anchors or anchor rods with foundation.

A full range of accessories is available.

Options

- Installation template + anchor rods (or base plate for chemical anchors, keeping its limitations in mind)
- Hoist power supply cable
- Lockable main switch
- Rotation slowing device (adaptable without welding or mechanical intervention)
- Option of a slowing device on each arm
- Hot dip galvanizing (contact us)
- Rotation stops to weld onto the assembly, or adjustable, on 1 arm
- Single- or multipositions rotation lock (arm 1 only)
- Outdoor use
- Electric or manual hoist

Part Code	WLL ton	Cap. kg	Span m 2,0	Span m 2,5	Span m 3,0	Span m 3,5	Span m 4,0	Span m 4,5	Span m 5,0
6025	0.125	125	•	•	•	•	•	•	•
6025	0.25	250	•	•	•	•	•	•	•

Technical data

Outreach (m) / Capacity (kg)	2	2,5	3	3,5	4	4,5	5	5,5
125	Х	x	Х	x	Х	x	Х	×
250	Х	Х	X	Х	X	Х	Х	X