



VR VARIO electric chain hoist

Product information

Code	WLL ton	Number of falls	Type	Chain Ø mm	Lifting speed m/min.	Duty Class	FEM Duty Class	ISO	table.heading.Gearbox-lifetime-hourstable.heading.ESR-loads-kgtable.heading.ESR-speeds-m-min	table.heading.ESR-loads-kgtable.heading.ESR-speeds-m-min	table.heading.ESR-loads-kgtable.heading.ESR-speeds-m-min
VR5 1224 V2	0.125	1	VR5 1224 V2	4 x 11	0.64 -> 24	2m	M5		1,600	80	32
VR5 2516 V2	0.25	1	VR5 2516 V2	4 x 11	0.64 -> 16	2m	M5		1,600	80	32
VR5 3212 V1	0.32	1	VR5 3212 V1	4 x 11	0.64 -> 12.5	1Am	M4		800	80	32
VR5 508 V2	0.5	1	VR5 508 V2	5 x 14	0.32 -> 8	2m	M5		1,600	160	16
VR12 5016 V2	0.5	1	VR12 5016 V2	7 x 20	0.63 -> 16	2m	M5		1,600	160	32
VR5 636 V1	0.63	1	VR5 636 V1	5 x 14	0.32 -> 6.5	1Am	M4		800	160	16
VR12 6312 V1	0.63	1	VR12 6312 V1	7 x 20	0.63 -> 12.5	1Am	M4		800	160	32
VR12 809 V2	0.8	1	VR12 809 V2	7 x 20	0.31 -> 9	2m	M5		1,600	320	16
VR12 1008 V2	1	1	VR12 1008 V2	7 x 20	0.31 -> 8	2m	M5		1,600	320	16
VR12 1256 V1	1.25	1	VR12 1256 V1	7 x 20	0.31 -> 6.5	1Am	M4		800	320	16
VR12 1604 V2	1.6	2	VR12 1604 V2	7 x 20	0.16 -> 4.5	2m	M5		1,600	630	8
VR12 2004 V2	2	2	VR12 2004 V2	7 x 20	0.16 -> 8	2m	M5		1,600	630	8
VR12 2503 V1	2.5	2	VR12 2503 V1	7 x 20	0.16 -> 16	1Am	M4		800	630	8