


Elevator



## PAWO 7S

### Product information



Special full steel rope with IWRC

In PAWO F7S the fiber component of the F7 steel core was replaced by a steel strand, thus achieving an even higher metallic cross-section plus an even higher breaking strength.

This full steel rope is primarily used in installations where the rope service life is more affected by the impact of permanent bends than by wear from the traction sheave. The steel wire rope core minimizes rope elongation in comparison to the types F3 and F7. As a consequence, the rope is particularly suitable for high-rise applications with many bending cycles.

#### Properties

- medium and high-rise
- intermediate to high number of bending cycles
- normal to heavy usage levels
- low stretch
- long service life

**Rope construction:** 8x19 Warrington with steel core.

**Marking:** According to standard

**Standard:** EN 12385-5

<b>Part Code</b>	<b>Rope Diameter,</b>	<b>Tensile strength</b>	<b>Min. Breaking force</b>	<b>Finish</b>	<b>Weight</b>
		<b>N/mm<sup>2</sup></b>	<b>kN.</b>		<b>kg/100m</b>
106100804020259	8	1,570	-	Bright	-
106100904020259	9	1,570	-	Bright	-
106101004020259	10	1,570	-	Bright	-
106101104020259	11	1,570	-	Bright	-
106101204020259	12	1,570	-	Bright	-
106101304020259	13	1,570	-	Bright	-
106101404020259	14	1,570	-	Bright	-
106101504020259	15	1,570	-	Bright	-
106101604020259	16	1,570	-	Bright	-
106101804020259	18	1,570	-	Bright	-
106101904020259	19	1,570	-	Bright	-
106102004020259	20	1,570	-	Bright	-