


Elevator



Trulift 6F

Product information



Also available in Warrington construction (6&6/6/1)
Excellent stretch characteristics

Features: High quality six strand lift rope

Material: High Carbon Steel

Marking: According to standard, On Termination ID and CE mark

Finish: Ungalvanised

Standard: EN 12385-5

Fill factor: 0.49

| Part Code | Rope Diameter, mm | Tensile strength N/mm ² | Steel area mm ² | Min. Breaking force, kN | Finish | Rope lay. | Weight kg/100m |
|-----------------|----------------------|---------------------------------------|-------------------------------|----------------------------|--------|-----------|-------------------|
| 106100604130069 | 6 | 1,370/1,770 | 13.8 | 17.8 | Bright | sZ | 13 |
| 106100654130069 | 6.5 | 1,370/1,770 | 16.2 | 20.9 | Bright | sZ | 15 |
| 106100704130069 | 7 | 1,370/1,770 | 18.8 | 24.3 | Bright | sZ | 18 |
| 106100804130069 | 8 | 1,370/1,770 | 24.6 | 31.7 | Bright | sZ | 23 |
| 106100904130069 | 9 | 1,370/1,770 | 31.1 | 40.1 | Bright | sZ | 29 |
| 106101004130069 | 10 | 1,370/1,770 | 38.4 | 49.5 | Bright | sZ | 36 |
| 106101104130069 | 11 | 1,370/1,770 | 46.5 | 59.9 | Bright | sZ | 43 |
| 106101204130069 | 12 | 1,370/1,770 | 55.3 | 71.3 | Bright | sZ | 52 |
| 106101304130069 | 13 | 1,370/1,770 | 64.9 | 83.7 | Bright | sZ | 61 |
| 106101404130069 | 14 | 1,370/1,770 | 75.3 | 97 | Bright | sZ | 70 |
| 106101504130069 | 15 | 1,370/1,770 | 86.4 | 111 | Bright | sZ | 81 |
| 106101604130069 | 16 | 1,370/1,770 | 98.3 | 127 | Bright | sZ | 92 |
| 106101904130069 | 19 | 1,370/1,770 | 139 | 179 | Bright | sZ | 130 |
| 106102204130069 | 22 | 1,370/1,770 | 186 | 240 | Bright | sZ | 174 |