

## Trulift 8F

### Product information



Also available in Filler (12/6&6F/1) and Warrington (6&6/6/1) constructions.  
Excellent stretch characteristics.

**Features:** High quality eight strand fibre core lift rope.

**Marking:** According to standard


**Finish:** Ungalvanised.

**Standard:** EN 12385-5

**Fill factor:** 0.44

**Tolerance Ø:** 0% to +6%

Elevator



Part Code	Rope Diameter, mm	Tensile strength N/mm <sup>2</sup>	Steel area mm <sup>2</sup>	Min. Breaking force kN.	Finish	Weight kg/100m
106100804130079	8	1,370/1,770	-	-	Bright	-
106100904130079	9	1,370/1,770	-	-	Bright	-
106101004130079	10	1,370/1,770	-	-	Bright	-
106101104130079	11	1,370/1,770	-	-	Bright	-
106101204130079	12	1,370/1,770	-	-	Bright	-
106101304130079	13	1,370/1,770	-	-	Bright	-
106101404130079	14	1,370/1,770	-	-	Bright	-
106101504130079	15	1,370/1,770	-	-	Bright	-
106101604130079	16	1,370/1,770	-	-	Bright	-
106101904130079	19	1,370/1,770	-	-	Bright	-
106102204130079	22	1,370/1,770	-	-	Bright	-