



SS 6x36WS-FC

Product information



Typical applications: Cranes, hoist blocks, lifts, wire rope slings.

Design: Ordinary right hand lay.

Rope construction: 6x36WS-FC Warrington-Seale.

Material: AISI 316.

Fill factor: 0,50

Part Code	Rope Diameter, mm	Tensile strength N/mm ²	Steel area mm ²	Min. Breaking force, kN	Finish	Rope lay.	Weight kg/100m
108100804620168	8	1,570	25.2	33	Stainless	sZ	24
108101004620168	10	1,570	39.3	51.6	Stainless	sZ	37
108101204620168	12	1,570	56.6	74.4	Stainless	sZ	53
108101404620168	14	1,570	77	101	Stainless	sZ	73
108101604620168	16	1,570	100	133	Stainless	sZ	95
108101804620168	18	1,570	127	168	Stainless	sZ	120
108102004620168	20	1,570	157	203	Stainless	sZ	148
108102204620168	22	1,570	190	250	Stainless	sZ	179
108102404620168	24	1,570	226	298	Stainless	sZ	214
108102604620168	26	1,570	266	340	Stainless	sZ	251
108102804620168	28	1,570	308	405	Stainless	sZ	291
108103004620168	30	1,570	353	464	Stainless	sZ	334