

## Steel Wire Rope 8x36WS-IWRC

### Product information



ISO 4309 Rope Category No: RCN.11

Rope construction: 8x36WS-IWRC.

Marking: According to standard

Standard: EN 12385-4


Fill factor: 0.6

RCN: 11

Winch rope



Overhead cranes



Tower crane



Part Code	Rope Diameter,	Tensile strength N/mm <sup>2</sup>	Finish	Rope lay.	Min. Breaking force kN	Steel area mm <sup>2</sup>	Lubrication	Weight kg/100m
101101304050091	13	1,770	Bright	sZ	106	79.1	A-1	70.5
101101303050091	13	1,770	Bright	zS	106	79.1	A-1	70.5
101101304250091	13	1,770	Galvanized	sZ	106	79.1	A-1	70.5
101101303250091	13	1,770	Galvanized	zS	106	79.1	A-1	70.5

101101304070091	13	1,960	Bright	sZ	118	79.1	A-1	70.5
101101303070091	13	1,960	Bright	zS	118	79.1	A-1	70.5
101101304270091	13	1,960	Galvanized	sZ	118	79.1	A-1	70.5
101101303270091	13	1,960	Galvanized	zS	118	79.1	A-1	70.5
101101404050091	14	1,770	Bright	sZ	124	91.7	A-1	81.7
101101403050091	14	1,770	Bright	zS	124	91.7	A-1	81.7
101101404250091	14	1,770	Galvanized	sZ	124	91.7	A-1	81.7
101101403250091	14	1,770	Galvanized	zS	124	91.7	A-1	81.7
101101404070091	14	1,960	Bright	sZ	137	91.7	A-1	81.7
101101403070091	14	1,960	Bright	zS	137	91.7	A-1	81.7
101101404270091	14	1,960	Galvanized	sZ	137	91.7	A-1	81.7
101101403270091	14	1,960	Galvanized	zS	137	91.7	A-1	81.7
101101604050091	16	1,770	Bright	sZ	161	120	A-1	107
101101603050091	16	1,770	Bright	zS	161	120	A-1	107
101101604250091	16	1,770	Galvanized	sZ	161	120	A-1	107
101101603250091	16	1,770	Galvanized	zS	161	120	A-1	107
101101604070091	16	1,960	Bright	sZ	179	120	A-1	107
101101603070091	16	1,960	Bright	zS	179	120	A-1	107
101101604270091	16	1,960	Galvanized	sZ	179	120	A-1	107
101101603270091	16	1,960	Galvanized	zS	179	120	A-1	107
101101804050091	18	1,770	Bright	sZ	204	152	A-1	135
101101803050091	18	1,770	Bright	zS	204	152	A-1	135
101101804250091	18	1,770	Galvanized	sZ	204	152	A-1	135

101101803250091	18	1,770	Galvanized	zS	204	152	A-1	135
101101804070091	18	1,960	Bright	sZ	226	152	A-1	135
101101803070091	18	1,960	Bright	zS	226	152	A-1	135
101101804270091	18	1,960	Galvanized	sZ	226	152	A-1	135
101101803270091	18	1,960	Galvanized	zS	226	152	A-1	135
101102004050091	20	1,770	Bright	sZ	252	187	A-1	167
101102003050091	20	1,770	Bright	zS	252	187	A-1	167
101102004250091	20	1,770	Galvanized	sZ	252	187	A-1	167
101102003250091	20	1,770	Galvanized	zS	252	187	A-1	167
101102004070091	20	1,960	Bright	sZ	279	187	A-1	167
101102003070091	20	1,960	Bright	zS	279	187	A-1	167
101102004270091	20	1,960	Galvanized	sZ	279	187	A-1	167
101102003270091	20	1,960	Galvanized	zS	279	187	A-1	167
101102204050091	22	1,770	Bright	sZ	305	227	A-1	202
101102203050091	22	1,770	Bright	zS	305	227	A-1	202
101102204250091	22	1,770	Galvanized	sZ	305	227	A-1	202
101102203250091	22	1,770	Galvanized	zS	305	227	A-1	202
101102204070091	22	1,960	Bright	sZ	338	227	A-1	202
101102203070091	22	1,960	Bright	zS	338	227	A-1	202
101102204270091	22	1,960	Galvanized	sZ	338	227	A-1	202
101102203270091	22	1,960	Galvanized	zS	338	227	A-1	202
101102404050091	24	1,770	Bright	sZ	363	270	A-1	240
101102403050091	24	1,770	Bright	zS	363	270	A-1	240

101102404250091	24	1,770	Galvanized	sZ	363	270	A-1	240
101102403250091	24	1,770	Galvanized	zS	363	270	A-1	240
101102404070091	24	1,960	Bright	sZ	402	270	A-1	240
101102403070091	24	1,960	Bright	zS	402	270	A-1	240
101102404270091	24	1,960	Galvanized	sZ	402	270	A-1	240
101102403270091	24	1,960	Galvanized	zS	402	270	A-1	240