

Steel Wire Rope POLYASS

Product information



Rope construction: 8 strands with steel wire core.

Marking: According to standard

Standard: EN 12385-4


Note: ISO 4309 Rope Category No: 6-26mm RCN 04

Fill factor: 0.58

Winch rope



Overhead cranes



Tower crane



Part Code	Rope Diameter,	Tensile strength N/mm ²	Finish	Rope lay.	Min. Breaking force kN	Steel area mm ²	Lubrication	Weight kg/100m
101100604270110	6	1,960	Galvanized	sZ	25.1	16.5	Dry	15
101100603270110	6	1,960	Galvanized	zS	25.1	16.5	Dry	15
101100604270111	6	1,960	Galvanized	sZ	25.1	16.5	A-1	15
101100603270111	6	1,960	Galvanized	zS	25.1	16.5	A-1	15

101100654050111	6.5	1,770	Bright	sZ	26.6	19.3	A-1	17
101100654270110	6.5	1,960	Galvanized	sZ	29.5	19.3	Dry	17
101100653270110	6.5	1,960	Galvanized	zS	29.5	19.3	Dry	17
101100654270111	6.5	1,960	Galvanized	sZ	29.5	19.3	A-1	17
101100653270111	6.5	1,960	Galvanized	zS	29.5	19.3	A-1	17
101100754070111	7.5	1,960	Bright	sZ	39.2	25.7	A-1	23
101100754270110	7.5	1,960	Galvanized	sZ	39.2	25.7	Dry	23
101100753270110	7.5	1,960	Galvanized	zS	39.2	25.7	Dry	23
101100754270111	7.5	1,960	Galvanized	sZ	39.2	25.7	A-1	23
101100753270111	7.5	1,960	Galvanized	zS	39.2	25.7	A-1	23
101100753070111	7.5	1,960	Bright	zS	49.2	25.7	A-1	23
101100804270110	8	1,960	Galvanized	sZ	49.2	29.2	Dry	26
101100803270110	8	1,960	Galvanized	zS	49.2	29.2	Dry	26
101100804270111	8	1,960	Galvanized	sZ	49.2	29.2	A-1	26
101100803270111	8	1,960	Galvanized	zS	49.2	29.2	A-1	26
101100804300111	8	2,160	Galvanized	sZ	49.2	29.2	A-1	26
101100904270110	9	1,960	Galvanized	sZ	56.5	37	Dry	33
101100903270110	9	1,960	Galvanized	zS	56.5	37	Dry	33
101100904270111	9	1,960	Galvanized	sZ	56.5	37	A-1	33
101100903270111	9	1,960	Galvanized	zS	56.5	37	A-1	33
101101004270110	10	1,960	Galvanized	sZ	69.8	45.7	Dry	41
101101003270110	10	1,960	Galvanized	zS	69.8	45.7	Dry	41
101101004270111	10	1,960	Galvanized	sZ	69.8	45.7	A-1	41

101101003270111	10	1,960	Galvanized	zS	69.8	45.7	A-1	41
101101103070111	11	1,960	Bright	zS	84.4	55.3	A-1	49
101101104270110	11	1,960	Galvanized	sZ	84.4	55.3	Dry	49
101101103270110	11	1,960	Galvanized	zS	84.4	55.3	Dry	49
101101104270111	11	1,960	Galvanized	sZ	84.4	55.3	A-1	49
101101103270111	11	1,960	Galvanized	zS	84.4	55.3	A-1	49
101101204270110	12	1,960	Galvanized	sZ	100	65.8	Dry	59
101101203270110	12	1,960	Galvanized	zS	100	65.8	Dry	59
101101204270111	12	1,960	Galvanized	sZ	100	65.8	A-1	59
101101203270111	12	1,960	Galvanized	zS	100	65.8	A-1	59
101101303250110	13	1,770	Galvanized	zS	106	77.2	Dry	69
101101304270110	13	1,960	Galvanized	sZ	118	77.2	Dry	69
101101303270110	13	1,960	Galvanized	zS	118	77.2	Dry	69
101101304270111	13	1,960	Galvanized	sZ	118	77.2	A-1	69
101101303270111	13	1,960	Galvanized	zS	118	77.2	A-1	69
101101404070111	14	1,960	Bright	sZ	137	89.6	A-1	80
101101404270110	14	1,960	Galvanized	sZ	137	89.6	Dry	80
101101403270110	14	1,960	Galvanized	zS	137	89.6	Dry	80
101101404270111	14	1,960	Galvanized	sZ	137	89.6	A-1	80
101101403270111	14	1,960	Galvanized	zS	137	89.6	A-1	80
101101504270111	15	1,960	Galvanized	sZ	157	103	A-1	92
101101503270111	15	1,960	Galvanized	zS	157	103	A-1	92
101101604270111	16	1,960	Galvanized	sZ	179	117	A-1	104

101101603270111	16	1,960	Galvanized	zS	179	117	A-1	104
101101704270111	17	1,960	Galvanized	sZ	202	132	A-1	118
101101703270111	17	1,960	Galvanized	zS	202	132	A-1	118
101101804270110	18	1,960	Galvanized	sZ	226	148	Dry	132
101101804270111	18	1,960	Galvanized	sZ	226	148	A-1	132
101101803270111	18	1,960	Galvanized	zS	226	148	A-1	132
101101904270110	19	1,960	Galvanized	sZ	252	165	Dry	147
101101904270111	19	1,960	Galvanized	sZ	252	165	A-1	147
101101903270111	19	1,960	Galvanized	zS	252	165	A-1	147
101102004270110	20	1,960	Galvanized	sZ	279	183	Dry	163
101102004270111	20	1,960	Galvanized	sZ	279	183	A-1	163
101102003270111	20	1,960	Galvanized	zS	279	183	A-1	163
101102204270111	22	1,960	Galvanized	sZ	338	221	A-1	197
101102203270111	22	1,960	Galvanized	zS	338	221	A-1	197
101102404270111	24	1,960	Galvanized	sZ	402	263	A-1	234
101102403270111	24	1,960	Galvanized	zS	402	263	A-1	234
101102604270111	26	1,960	Galvanized	sZ	472	309	A-1	275
101102603270111	26	1,960	Galvanized	zS	472	309	A-1	275