



Wire Rope Lifting Sling WLS-002

Product information

Standard steel wire rope construction: 6x36WS IWRC, 1960N/mm2*

(*ø 3mm - ø 7mm rope construction: 6x19M WSC 1960 N/mm2)

Design: Endless with master link and mechanical aluminium spliced thimbles.

Load table at Technical Data -> Show table

Please specify the needed (working) length with your request.

Other rope constructions possible on request. In that case, please contact us to discuss the possible options or specify it with your request.

Note: We recommend that the sling not is bent over a diameter less than 6 times the wire rope diameter without reducing the WLL.

Part Code	WLL ton
1601	0.23
1601	0.42
1601	0.65
1601	0.94
1601	1.28
1601	1.64
1601	2.07
1601	2.56

1601	3.1
------	-----

1601	3.67
------	------

1601	4.33
------	------

1601	5.03
------	------

1601	6.57
------	------

1601	8.3
------	-----

1601	10.24
------	-------

1601	12.41
------	-------

1601	16.8
------	------

1601	17.33
------	-------

1601	17.46
------	-------

1601	20.08
------	-------

1601	26.25
------	-------

1601	33.19
------	-------

1601	41.11
------	-------

1601	49.56
------	-------

1601	59.1
------	------

1601	69.38
------	-------

Technical data