



General use



Steel Wire Rope PVC-coated 6x7-FC

Product information



A galvanized rope equipped with a Fibre Core (FC) and has a PVC-coating. It can be used for various applications such as locking rope, signaling devices, etc but not for lifting.

The PVC-coating is UV stabilized which makes it suitable for longterm outdoor use and it is fully compliant with REACH Directive 1907/2006.

Rope construction: 6x7-FC

Marking: According to standard

Temperature range: -30°C up to +70°C

Finish: PVC-coated, see table for colour

Standard: EN 12385-4

except from coating

Note: Peel off coating at end when making any end fittings such as clamping ferrules etc.

Fill factor: 0,47

Part Code	Rope Diameter,	Inner diameter	Colour	Tensile strength	Min. Breaking force	Steel area	Lubrication	Weight
	mm	mm		N/mm ²	kN	mm ²		kg/100m
105130250150070	2.5	1.5	transparent	1,770	1.32	0.83	-	0.78
105140250150070	2.5	1.5	transparent	1,960	1.46	0.83	-	0.78
105130300200070	3	2	transparent	1,770	2.35	1.48	-	1.38
105130300200072	3	2	Red	1,770	2.35	1.48	-	1.38

105140300200070	3	2	transparent	1,960	2.6	1.48	-	1.38
105140300200072	3	2	Red	1,960	2.6	1.48	-	1.38
105130400300070	4	3	transparent	1,770	5.29	3.32	-	3.11
105130400300072	4	3	Red	1,770	5.29	3.32	-	3.11
105140400300070	4	3	transparent	1,960	5.86	3.32	-	3.11
105140400300072	4	3	Red	1,960	5.86	3.32	-	3.11
105130450300070	4.5	3	transparent	1,770	5.29	3.32	-	3.11
105140450300070	4.5	3	transparent	1,960	5.86	3.32	-	3.11
105130500400070	5	4	transparent	1,770	9.4	5.9	-	5.54
105130500400072	5	4	Red	1,770	9.4	5.9	-	5.54
105140500400070	5	4	transparent	1,960	10.4	5.9	-	5.54
105140500400072	5	4	Red	1,960	10.4	5.9	-	5.54
105130600400070	6	4	transparent	1,770	9.4	5.9	-	5.54
105140600400070	6	4	transparent	1,960	10.4	5.9	-	5.54
105130600500070	6	5	transparent	1,770	14.7	9.23	-	8.63
105130700500070	7	5	transparent	1,770	14.7	9.23	-	8.63
105140700500070	7	5	transparent	1,960	16.3	9.23	-	8.63
105130800600070	8	6	transparent	1,770	21.2	13.3	-	12.5
105140800600070	8	6	transparent	1,960	23.4	13.3	-	12.5