



SS 6x36 IWRC

Product information

sZ zS SS

Stainless steel wire rope.

Design: Cross lay right-handed, alternative design on request.

Rope construction: 6x36 IWRC.

Material: AISI 316/1570 N/mm²

Part Code	Rope Diameter, mm	Tensile strength N/mm ²	Finish	Rope lay.	Min. Breaking force kN	Steel area mm ²	Lubrication	Weight kg/100m
108100804620178	8	1,570	Stainless	sZ	36.6	-	No-Lube	27
108100803620178	8	1,570	Stainless	zS	36.6	-	No-Lube	27
108101004620178	10	1,570	Stainless	sZ	56.9	-	No-Lube	42
108101003620178	10	1,570	Stainless	zS	56.9	-	No-Lube	42
108101204620178	12	1,570	Stainless	sZ	80.6	-	No-Lube	60.2
108101203620178	12	1,570	Stainless	zS	80.6	-	No-Lube	60.2
108101304620178	13	1,570	Stainless	sZ	94.8	-	No-Lube	70.7
108101303620178	13	1,570	Stainless	zS	94.8	-	No-Lube	70.7
108101404620178	14	1,570	Stainless	sZ	109	-	No-Lube	82
108101403620178	14	1,570	Stainless	zS	109	-	No-Lube	82
108101504620178	15	1,570	Stainless	sZ	125.8	-	No-Lube	94.5
108101503620178	15	1,570	Stainless	zS	125.8	-	No-Lube	94.5
108101604620178	16	1,570	Stainless	sZ	142	-	No-Lube	107
108101603620178	16	1,570	Stainless	zS	142	-	No-Lube	107
108101804620178	18	1,570	Stainless	sZ	180	-	No-Lube	135
108101803620178	18	1,570	Stainless	zS	180	-	No-Lube	135
108102004620178	20	1,570	Stainless	sZ	221	-	No-Lube	167
108102003620178	20	1,570	Stainless	zS	221	-	No-Lube	167
108102204620178	22	1,570	Stainless	sZ	271	-	No-Lube	198
108102404620178	24	1,570	Stainless	sZ	321	-	No-Lube	241
108102403620178	24	1,570	Stainless	zS	321	-	No-Lube	241