



Stay rope



## Spiral Strand 1x19 Stainless

### Product information



**Typical applications:** Wire rope for rigging, stays and controls.

**Design:** Right- or left-handed.

**Rope construction:** 1x19

**Material:** AISI 316

**Marking:** According to standard

**Standard:** EN 12385-10

*except material*

**Fill factor:** 0.76

Part Code	Rope Diameter, mm	Tensile strength N/mm <sup>2</sup>	Finish	Rope lay.	Min. Breaking force kN	Steel area mm <sup>2</sup>	Lubrication	Weight kg/100m
108100101620078	1	1,570	Stainless	S	0.82	-	No-Lube	0.5
108100102620078	1	1,570	Stainless	Z	0.82	-	No-Lube	0.5
108100152620078	1.5	1,570	Stainless	Z	1.86	-	No-Lube	1.1
108100252620078	2.5	1,570	Stainless	Z	5.16	-	No-Lube	3.05
108101402620078	14	1,570	Stainless	Z	162	-	No-Lube	95.1
108101602620078	16	1,570	Stainless	Z	211	-	No-Lube	124
108102901620078	29	1,570	Stainless	S	694	-	No-Lube	408
108102902620078	29	1,570	Stainless	Z	694	-	No-Lube	408
108103001620078	30	1,570	Stainless	S	743	-	No-Lube	436