



## Snatch Block S - Schackle |Discontinued

### Product information

**General:** Intended for general lifting purposes. Can also be used for pulling. WLL in table applies for load on head fitting/shackle.

**Features:**

- Snatch block type with covering side plates.
- Provided with swiveling bow shackle.
- Grease fitting in the shaft and cross head.
- Bronze bushed sheave in 2-4 tons blocks and roller bearings in larger sizes.

**Material:** Steel.

**Marking:** Type, WLL and wire rope diameter.

**Finish:** Blue painted.

Part Code	Rope Ø range	WLL ton	TA mm	TB mm	TC mm	Ø D1 mm	Ø D2 mm	Weight kg
424100200080	7-9	2	82	70	290	75	58	4
424100400080	10-12	4	120	70	358	115	90	6
424100400085	16-19	4	160	70	432	150	120	14
424100800080	19-22	8	210	93	550	200	165	16
424101000080	24-26	10	260	115	681	250	205	38
424101200080	24-26	12	310	133	767	300	250	56
424101500087	22-24	15	210	102	663	200	165	24
424101500080	24-26	15	310	133	788	300	250	65
424102200080	28-32	22	365	140	962	355	305	90
424103000080	28-30	30	310	193	1,023	300	245	125
424103000086	32-35	30	415	155	1,121	405	350	135
424103500080	32-35	35	365	193	1,058	350	280	130
424105000080	46-50	50	625	275	1,525	600	500	418

# Blueprint

