



## Crane Lift Basket BK-500 / BK-1000 / BK-1000E (Emergency)

### Product information



Man riding baskets can be used quickly and safely for temporary working at heights. Our man riding baskets are designed to be hung from a crane hook.

If the basket is exposed to corrosive environment, we recommend additional treatment according to Offshore coating system.

**Storage:** For increased longevity, we recommend that the basket is stored in-doors in a dry environment.”

**Design:** Welded frame in hollow beam with the bottom and sides covered in expanded-metal mesh. Personal items of safety equipment can be attached to the inside handrail. The basket is supported underneath for easy handling by truck or forklift. A gate is provided on one of the short sides (see the respective model). The basket is supplied complete with a four leg wire rope sling and a masterlink type MLA.

**BK-500:** Supplied with inward-opening latching gate.

**BK-1000:** Supplied with inward-opening latching gate.

**BK-1000E (Emergency):** Identical to the BK-500 / BK-1000 above except that in an emergency the entire end gate can be opened outwards to provide access, eg, for a stretcher and medical equipment to be taken on board.

**Material:** Hollow-beam and plate of high-strength structural steel.

**Marking:** Sign according to standard for inspection mark.

**Finish:** Yellow protective painting, RAL 1003, corrosivity class C3 (indoor storage), other painting programs are quoted upon request.

| Part Code   | Code     | WLL ton | Basket weight kg | Max. number of persons | A mm  | B mm  | E mm | H mm  | L mm  | Weight kg |
|-------------|----------|---------|------------------|------------------------|-------|-------|------|-------|-------|-----------|
| 6211BK0500  | BK-500   | 0.5     | 220              | 2                      | 1,240 | 1,000 | 600  | 2,000 | 3,100 | 720       |
| 6211BK1000  | BK-1000  | 1       | 350              | 4                      | 2,000 | 1,200 | 700  | 2,100 | 4,470 | 1,350     |
| 6211BK1000E | BK-1000E | 1       | 400              | 4                      | 2,300 | 1,200 | 700  | 2,100 | 4,700 | 1,400     |

## Blueprint

