

## **Swivel Hook Crosby S-1326**

## **Product information**

## Features:

- Individually Proof Tested at 2-1/2 times the 4:1 Working Load Limit with certification.
- Recessed trigger design is flush with the hook body, protecting the trigger from potential damage.
- Easy to operate with enlarged thumb access.
- Positive Lock Latch is Self-Locking when hook is loaded.
- Rated for both Wire Rope and use with Grade 80/100 Chain.

Material: Forged Alloy Steel - Quenched and Tempered.

Finish: Painted

Safety factor: 4:1 Grade: 10

Part Code	WLL ton	Chain mm	A mm	B mm	C mm	D mm	E mm	F mm	H mm	J mm	L mm	AA** mm	Weight kg
402300151400	1.45	6	38.1	33.5	156	20.1	66	17	12.7	16	28.7	38.1	0.57
402300261400	2.6	7-8	44.5	40.4	193	27.9	88.9	22.1	16	20.6	35.1	51	1.18
402300401400	4	10	50.8	43.9	224	29.7	112	27.9	19.1	23.9	44.5	63.5	2.13
402300681400	6.8	13	63.5	60.5	284	42.4	139	32	25.4	29.5	53.6	76.2	3.92
402301031400	10.3	16	69.9	64.3	328	51.8	167	38.1	28.7	38.1	63.2	89	7.71
402301601400	16	18-20	71.9	64	358	56.4	197	51.1	27.9	51.6	89.4	127	10.9
402302001400	20	22	87.4	81	417	62.2	222	57.4	33	55.9	97.3	152	13.2

## Blueprint

