



Lever Hoist Elephant YII

Product information

YII Series lever hoists are extremely versatile, suitable for lifting and pulling in many applications.

A solid and compact design with special rust-resistant coating performs in extreme environments such as the offshore and mining industries. Extremely lightweight [9.5kg (1.6 Tonne)] The gears are completely enclosed and make the hoist highly reliable and durable meaning lower maintenance costs. One-touch change lever further improves work efficiency. Tough black body resists scratches and prevents rust. Waterproof, shock resistant gear and brake cover. The bolted rubber grip ensures safe operation of the lever hoist.

Material: Chain and hook, alloy steel grade 10.

Marking: WLL, code and CE marking.

Finish: Painted.

Safety factor: 5:1

Part Code	Code	WLL ton	Lifting height m	Min Headroom mm	Hook Opening mm	Lever length mm	Load chain Ø mm	Number of falls	Weight kg
500500030150010	YII-25	0.25	1.5	235	20	155	4	1	2
500500050150010	YII-50	0.5	1.5	265	23	284	5	1	3.6
500500080150010	YII-80	0.8	1.5	290	25	268	5,6	1	6.2
500500160150010	YII-160	1.6	1.5	350	29	385	7,2	1	9.5
500500320150010	YII-320	3.2	1.5	420	36	385	9,0	1	15.5
500500630150010	YII-640	6.3	1.5	570	45	385	9,0	2	26.5

Blueprint

