



## Master Link Pewag AW

### Product information

AW Master links are designed for the assembly of chain slings. For pewag connex and welded system.

Master link for 1-leg chain AI.

Master link for 2-leg chain AII.

Master link for 3- and 4-leg chain AIII/IV - only with transition link BW as on VW.

Can also be used as end link A I

**Material:** High duty

**Marking:** According to standard, CE-marked, Pewag or PW, winner or 10, H16, batch code and type.

**Temperature range:** -40°C up to +380°C.

**Finish:** Orange powder coated.

**Standard:** EN 1677-4

**Safety factor:** 4:1

**Grade:** 10

Part Code	Code	WLL ton	LC kN	EWL	For chain Ø 1-leg AW I mm	For chain Ø 2-leg AW II mm	Single hook DIN 15401 no.	Double hook DIN 15402 no.	d mm	s mm	t mm	w mm	Weight kg
402100140290	AW 10	1.4	28	80	5	5	1.6	2.5	10	10	80	50	0.14
402100230290	AW 13	2.3	46	110	6+7	6	2.5	4	13	10	110	60	0.34
402100350290	AW 16	3.5	70	110	8	7	2.5	4	16	14	110	60	0.53
402100500290	AW 18	5	100	135	10	8	5	6	19	14	135	75	0.92
402100760290	AW 22	7.6	152	160	13	10	6	8	23	17	160	90	1.6
402101000290	AW 26	10	200	180	16	13	8	10	27	20	180	100	2.46
402101400290	AW 32	14	280	200	19	16	10	12	33	26	200	110	4.14
402102510290	AW 36	25.1	502	260	22	19	16	20	36	29	260	140	6.22
402103080290	AW 45	30.8	616	340	26	22	25	32	45	-	340	180	12.82
402104000290	AW 50	40	800	350	32	26	32	40	50	43	350	190	16.55
402106400290	AW 56	64	1,277	400	-	32	32	40	56	-	400	200	27.01
402108500290	AW 72	85	1,700	460	-	-	50	63	70	-	460	250	45.3

# Blueprint

